



Level TROLL® Instruments

Water Level Instruments for
Every Application & Budget



Level TROLL® 700 Instrument

- Optimized for aquifer characterization
- Gauged (vented) and absolute (non-vented) instruments
- Linear, fast linear, linear average, event, step linear, and true logarithmic logging modes
- Rugged titanium probe and sensor (OD: 1.83 cm; 0.72 in)

Level TROLL® 500 Instrument

- Ideal for groundwater and surface-water monitoring
- Gauged and absolute instruments
- Linear, fast linear, and event logging modes
- Durable titanium probe and sensor (OD: 1.83 cm; 0.72 in)

Level TROLL® 300 Instrument

- Suitable for fresh water and industrial monitoring
- Absolute instrument
- Linear, fast linear, and event logging modes
- Stainless steel probe and sensor (OD: 2.08 cm; 0.82 in)

Powerful, Accurate, Reliable Performance

- **Superior accuracy**—For guaranteed accuracy under all operating conditions, instruments undergo extensive calibration procedures for pressure and temperature. Each instrument includes a serialized calibration report.
- **Telemetry and SCADA integration**—Access data when you need it. No adapters or confusing proprietary protocols are required. Outputs include standard Modbus/RS485, SDI-12, and 4-20 mA.
- **Low power consumption**—Batteries have a typical life of 10 years or 2 million readings. 8-36 VDC input is compatible with external batteries and solar power.
- **Intuitive interface**—Win-Situ® 5 and Win-Situ® Mobile Software simplify data collection and management. Software features setup wizards, fast data download rates, multiple water level reference options, and more.

Applications

- Aquifer characterization
- Coastal deployments—tide/harbor levels, storm surge systems, and wetlands research
- Construction and mine dewatering
- River, lake, and reservoir monitoring
- Stormwater management

Level TROLL® 300, 500 & 700 Instruments

General	Level TROLL 300	Level TROLL 500	Level TROLL 700	BaroTROLL
Temperature ranges¹	Operational: -20-80° C (-4-176° F) Storage: -40-80° C (-40-176° F) Calibrated: -5-50° C (23-122° F)	Operational: -20-80° C (-4-176° F) Storage: -40-80° C (-40-176° F) Calibrated: -5-50° C (23-122° F)	Operational: -20-80° C (-4-176° F) Storage: -40-80° C (-40-176° F) Calibrated: -5-50° C (23-122° F)	Operational: -20-80° C (-4-176° F) Storage: -40-80° C (-40-176° F) Calibrated: -5-50° C (23-122° F)
Diameter	2.08 cm (0.82 in)	1.83 cm (0.72 in)	1.83 cm (0.72 in)	1.83 cm (0.72 in)
Length	22.9 cm (9.0 in)	21.6 cm (8.5 in)	21.6 cm (8.5 in)	21.6 cm (8.5 in)
Weight	245 g (0.54 lb)	197 g (0.43 lb)	197 g (0.43 lb)	197 g (0.43 lb)
Materials	Stainless steel body; Delrin® nose cone	Titanium body; Delrin nose cone	Titanium body; Delrin nose cone	Titanium body; Delrin nose cone
Output options	Modbus/RS485, SDI-12, 4-20 mA	Modbus/RS485, SDI-12, 4-20 mA	Modbus/RS485, SDI-12, 4-20 mA	Modbus/RS485, SDI-12, 4-20 mA
Battery type & life²	3.6V lithium; 10 years or 2M readings	3.6V lithium; 10 years or 2M readings	3.6V lithium; 10 years or 2M readings	3.6V lithium; 10 years or 2M readings
External power	8-36 VDC	8-36 VDC	8-36 VDC	8-36 VDC
Memory	1.0 MB	2.0 MB	4.0 MB	1.0 MB
Data records³	65,000	130,000	260,000	65,000
Data logs	2	50	50	2
Log types	Linear, Fast Linear, and Event	Linear, Fast Linear, and Event	Linear, Fast Linear, Linear Average, Event, Step Linear, True Logarithmic	Linear
Fastest logging rate & Modbus rate	2 per second	2 per second	4 per second	1 per minute
Fastest SDI-12 & 4-20 mA output rate	1 per second	1 per second	1 per second	1 per second
Real-time clock	Accurate to 1 second/24-hr period	Accurate to 1 second/24-hr period	Accurate to 1 second/24-hr period	Accurate to 1 second/24-hr period
Sensor Type/Material	Piezoresistive; stainless steel	Piezoresistive; titanium	Piezoresistive; titanium	Piezoresistive; titanium
Range	<i>Absolute (non-vented)</i> 30 psia: 10.9 m (35.8 ft) 100 psia: 60.1 m (197.3 ft) 300 psia: 200.7 m (658.7 ft)	<i>Absolute (non-vented)</i> 30 psia: 10.9 m (35.8 ft) 100 psia: 60.1 m (197.3 ft) 300 psia: 200.7 m (658.7 ft) 500 psia: 341.3 m (1120 ft) <i>Gauged (vented)</i> 5 psig: 3.5 m (11.5 ft) 15 psig: 11 m (35 ft) 30 psig: 21 m (69 ft) 100 psig: 70 m (231 ft) 300 psig: 210 m (692 ft) 500 psig: 351 m (1153 ft)	<i>Absolute (non-vented)</i> 30 psia: 10.9 m (35.8 ft) 100 psia: 60.1 m (197.3 ft) 300 psia: 200.7 m (658.7 ft) 500 psia: 341.3 m (1120 ft) 1000 psia: 703 m (2306.4 ft) <i>Gauged (vented)</i> 5 psig: 3.5 m (11.5 ft) 15 psig: 11 m (35 ft) 30 psig: 21 m (69 ft) 100 psig: 70 m (231 ft) 300 psig: 210 m (692 ft) 500 psig: 351 m (1153 ft)	0 to 16.5 psi; 0 to 1.14 bar
Burst pressure	Max. 2x range; burst > 3x range	Max. 2x range; burst > 3x range	Max. 2x range; burst > 3x range	Vacuum/over-pressure above 16.5 psi damages sensor
Accuracy @ 15° C⁴	±0.1% full scale (FS)	±0.05% FS	±0.05% FS	±0.1% FS
Accuracy (FS)⁵	±0.2% FS	±0.1% FS	±0.1% FS	±0.2% FS
Resolution	±0.01% FS or better	±0.005% FS or better	±0.005% FS or better	±0.005% FS or better
Units of measure	Pressure: psi, kPa, bar, mbar, mmHg, inHg, cmH ₂ O, inH ₂ O Level: in, ft, mm, cm, m	Pressure: psi, kPa, bar, mbar, mmHg, inHg, cmH ₂ O, inH ₂ O Level: in, ft, mm, cm, m	Pressure: psi, kPa, bar, mbar, mmHg, inHg, cmH ₂ O, inH ₂ O Level: in, ft, mm, cm, m	Pressure: psi, kPa, bar, mbar, mmHg, inHg, cmH ₂ O, inH ₂ O
Temperature Sensor				
Accuracy & resolution	±0.1° C; 0.01° C or better	±0.1° C; 0.01° C or better	±0.1° C; 0.01° C or better	±0.1° C; 0.01° C or better
Units of measure	Celsius or Fahrenheit	Celsius or Fahrenheit	Celsius or Fahrenheit	Celsius or Fahrenheit
Warranty	1 year	2 years	2 years	2 years
	Up to 5-year extended warranties are available for all instruments—call for details			

BaroTROLL® Instrument

The titanium BaroTROLL measures and logs barometric pressure and temperature. Use the BaroTROLL in conjunction with Level TROLL Instruments.

Win-Situ® Baro Merge™

Software simplifies post-correction of water level data.

Barometric readings are automatically subtracted from data collected by an absolute Level TROLL to compensate for changes in pressure due to barometric fluctuations.

24/7 Support

In-Situ technical support specialists assist with instrument setup, application support, and troubleshooting. Call for free technical support.

¹ Temperature range for non-freezing liquids

² Typical battery life when used within the factory-calibrated temperature range.

³ 1 data record = date/time plus 2 parameters logged (no wrapping) from device within the factory-calibrated temperature range

⁴ Across factory-calibrated pressure range

⁵ Across factory-calibrated pressure and temperature ranges

Specifications are subject to change without notice.

Delrin is a registered trademark of E.I. du Pont de Nemours and Company.

